



TYPE APPROVAL CERTIFICATE

Certificate No. : CWN04436-PE001 **Initial Approval** : 3rd February, 1993
Product : Mechanical Joints
Manufacturer : YOUNGNAM METAL CO., LTD.
900-3, Chojeun-ri, Chillye-myeon, Gimhae-si, Kyeongnam, Korea

Product Description :

Model	Type of joint	Nominal Diameter
GR-S (Grip Ring Standard)	Slip-on joints	15A - 350A
GR-L (Grip Ring Long)	Grip type	15A - 300A
MF-RS (Multi Flex Round Standard)		15A - 500A
MF-RL (Multi Flex Round Long)		15A - 500A
RCH-S (Round Clamp Hinge Standard)	Slip-on joints	15A - 500A
RCH-L (Round Clamp Hinge Long)	Slip type	15A - 500A
RCH-E (Round Clamp Hinge Elbow)		15A - 150A
RCD-E (Round Clamp Double Lock)		200A - 500A

" See Appendix 1 "

Approval Condition : " See Appendix 1 "

THIS IS TO CERTIFY that the above-mentioned product has been approved in accordance with the relevant requirement of this Society's Rules and / or of the recognized standards as follows.

Pt 5, Ch 6, Sec 1 of the Rules for the Classification of Steel Ships

This Certificate is valid until 2nd February, 2023
Reissued at Busan, Korea on 1st September, 2020



This certificate is signed electronically in accordance with IMO FAL.5/Circ.39/Rev.2. Validation and authentication of the certificate can be confirmed from "http://e-cert.krs.co.kr" by using the tracking No (ME20031523066) and certificate No.(CWN04436-PE001).



KOREAN REGISTER

*General Manager of
Marine & Ocean Equipment Team*

- Note** :
1. This certificate will be valid subject to complying with the approval conditions described on the certificate and/or on the Rules of this Society.
 2. This certificate will be invalid from the expiry date aforementioned unless the extension or renewal has been granted to the applicant or the manufacturer.
 3. Any significant modifications or changes in design or construction to the above product without approval from this Society will render this certificate invalid.
 4. Should the specified rules, regulations or standards be amended during the validity of this certificate, the product is to be re-approved by this Society in accordance with the requirements as amended.

Appendix 1

Product Description and/or Approval Condition

Certificate No : CWN04436-PE001

Date of Issue : 1st September, 2020

A. Product Description

1. Product Specification

1) Max. Working Pressure

Type	Normal Diameter (A)	Max. Working Pressure (bar)	Type	Normal Diameter (A)	Max. Working Pressure (bar)
MF-RS	15 - 40	20	MF-RS	200 - 250	10
	50 - 65	18		300 - 350	8
	80 - 100	16		400 - 450	5
	125 - 150	14		500	4
MF-RL	15 - 40	20	MF-RL	200 - 250	10
	50 - 65	18		300 - 350	8
	80 - 100	16		400 - 450	5
	125 - 150	14		500	4
GR-S	15 - 40	20	GR-S	125 - 150	14
	50 - 65	18		200 - 250	12
	80 - 100	16		300 - 350	10
GR-L	15 - 40	20	GR-L	125 - 150	14
	50 - 65	18		200 - 250	12
	80 - 100	16		300	10
RCH-S	15 - 25	14	RCH-S	200 - 250	7
	32 - 40	12		300 - 350	6
	50 - 65	10		400 - 450	4
	80 - 150	8		500	3
RCH-L	15 - 25	14	RCH-L	200 - 250	7
	32 - 40	12		300 - 350	6
	50 - 65	10		400 - 450	4
	80 - 150	8		500	3
RCH-E	15	11	RCD-E	200 - 250	6
	20 - 40	8		300 - 400	5
	50 - 150	7		450	4
			500	3	

2) Material

- Body : SUS 304, SUS 316L
- Rubber Packing : EPDM, NBR, Silicon, VITON

3) Temperature Range

- EPDM : -20 °C to 100 °C
- NBR : -20 °C to 80 °C
- Silicon : -60 °C to 200 °C
- VITON : -20 °C to 200 °C

2. Approved Drawings and Documents

- 1) Product catalogue and drawings intended for MF-RS, MF-RL, GR-S, GR-L, RCH-S, RCH-L, RCH-E and RCD-E series as followings ;
 - GR-S/L : YG-0002-0~2 dated 31 Aug 2020
 - GR-S/L : YG-5001 dated 24 July 2002
 - MF-RS/RL : YM-0001-0~2 dated 21 May 2019
 - RCH-S/L : YR-0003-0~2 dated 21 May 2019
 - RCH-E/RCD-E : YR-0004-0~2 dated 21 May 2019

3. Test Reports, etc.

- 1) Type test report No. 07T179 - 07T190 carried out at KOMERI.
- 2) Type test report intended for MF-RS, MF-RL, RCH-S, RCH-L, RCH-E and RCD-E series dated 25 Oct.2019 in the presence of KR Surveyor.
 - Tightness Test, Burst Pressure Test, Vacuum Test

Appendix 1

Product Description and/or Approval Condition

Certificate No : CWN04436-PE001

Date of Issue : 1st September, 2020

- Fire Endurance Test for MF-RS and MF-RL (except RCH-S, RCH-L, RCH-E and RCD-E)
- 3) Type test report intended for GR-S, GR-L series dated 17 Oct.2019.
 - Tightness Test, Burst Pressure Test, Vacuum Test
 - Fire Endurance Test for GR-S/L

B. Approval Condition

1. Application & Limitation

- 1) The mechanical joints can be used in easily visible and accessible positions for the following pipeline lines under the conditions tested :

	Application
① Flammable fluids(Flash point \leq 60 °C)	
- Cargo oil lines	(4)
- Crude oil washing lines	(4)
- Vent lines	(3)
② Inert gas	
- Water seal effluent lines	
- Scrubber effluent lines	
- Main lines	(2)(4)
- Distributions lines	(4)
③ Flammable fluids (Flash point $>$ 60 °C)	
- Cargo oil lines	(4)
- Fuel oil / Lubricating oil lines	(2)(3)
- Hydraulic oil / Thermal oil	(2)(3)
④ Sea Water	
- Bilge lines	(1)
- Water filled fire extinguishing systems (e.g. sprinkler systems)	(3)
- Non water filled fire extinguishing systems (e.g. foam, drencher systems)	(3)
- Fire main (not permanently filled)	(3)
- Ballast / Cooling water system	(1)
- Tank cleaning services / Non-essential systems	
⑤ Fresh water	
- Cooling water system	(1)
- Condensate return	(1)
- Non-essential system	
⑥ Sanitary / Drains / Scuppers	
- Deck drains (internal)	(4)(6)
- Sanitary drains / Scuppers and discharge (overboard)	
⑦ Sounding / Vent	
- Water tanks / Dry spaces	
- Oil tanks (flash point $>$ 60 °C)	(2)(3)
⑧ Miscellaneous	
- Starting / Control air	(1)
- Service air (non-essential)	
- Brine	
- CO2 system	(1)
- Steam	(5)

Appendix 1

Product Description and/or Approval Condition

Certificate No : CWN04436-PE001

Date of Issue : 1st September, 2020

※ NOTES

- (1) Inside machinery spaces of category A – approved fire resistant types.
- (2) Not accepted inside machinery spaces of category A or accommodation spaces.
May be accepted in other machinery spaces provided the joints are located in easily visible and accessible positions.
- (3) Approved fire resistant types except in cases where such mechanical joints are installed on open decks, as defined in SOLAS II-2/Reg. 9.2.3.3.2.2(10) and not used for fuel oil lines.
- (4) In pump rooms and open decks – approved fire resistant types.
- (5) Slip type of Slip-on joints may be used for pipes on deck with a design pressure of 10 bar or less.
- (6) Only above bulkhead deck of passenger ships and freeboard deck of cargo ships.

2) Limitations

- (1) RCH-S, RCH-L, RCH-E and RCD-E series are not approved as fire resistant type since they have not been tested for fire resistance.
- (2) EPDM material is not to be used with fuel oil and cargo oil. Material of mechanical joints is to be compatible with the piping material and internal and external media.
- (3) These mechanical joints are not to be used for Class I piping system.
- (4) These mechanical joints, which in the event of damage could cause fire or flooding, are not to be used in piping sections directly connected to the ship's side below the bulkhead deck of passenger ships and freeboard deck of cargo ships or tanks containing flammable fluids.
- (5) These mechanical joints are not to be used in pipelines in cargo holds, tanks and other spaces which are not easily accessible. Application of these inside tanks may be permitted only for the same media that is in the tanks.
- (6) These mechanical joints are not to be used in pipe systems where pressure pulsation other than water hammer is expected.
- (7) Where the application of mechanical joint results in reduction in pipe wall thickness, this is to be taken into account in determining the minimum wall thickness of the pipe to withstand the design pressure.
- (8) Any significant changes in design or construction of the products may render this certificate invalid.

2. Individual Product Cert. and Drawing Approval Requirement

- 1) Individual Product Certification is required where the mechanical joints are intended to be used for Class II piping system.

3. Marking

For traceability to this type approval, the couplings are at least to be marked with ;

- 1) Manufacturer's name or trademark
- 2) Date of manufacture (month/year)
- 3) Type designation
- 4) Nominal diameter, Pressure rating, Temperature rating

4. Others

Not applicable

< End of Certificate >